

V-SCRUB R.E.S.

Heavy Duty Acidic Cleaner for Rust , Efflorescence, and Leaf Stains

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

DRYLOK Etch cleans and etches concrete, stone, tile and brick. DRYLOK Etch removes efflorescence (salt-like deposits) and excess mortar. It's perfect for etching concrete and galvanized surfaces prior to painting. Safer to use than muriatic acid.

RECOMMENDED USES

Clean and etch interior and exterior concrete, stone, tile galvanized metal and brick.

- Prepares smooth concrete for painting
- Removes efflorescence
- Cleans mortar from brick and tile
- Conditions galvanized surfaces for painting
- No harmful fumes, safer and easier than muriatic acid
- Can be used indoors

APPLICATION & USAGE:

Surface Preparation: Remove dirt, dust, grease and oil by washing with heavy duty cleaner, such as V-SCRUB HD. Allow surface to dry.

Mixing: To remove rust, efflorescence and leaf stains dissolve 16 oz of V-SCRUB R.E.S. into 1 gallon of warm water. To etch concrete as preparation for sealing or coating dissolve 16 oz of V-SCRUB R.E.S. into ½ gallon of warm water. Do not use a galvanized container. Skin and eye protection is advised.

Application: To remove rust, efflorescence, or leaf stains apply V-SCRUB RES with a roller or sprayer. Allow to dwell 5-30 minutes. Brush with stiff broom. Flush very, very thoroughly with clean water. Repeat if necessary.

PACKAGING

2 lb Concentrate

COVERAGE

Use as required up to 300 ft.²/gal.

LIMITATIONS

Do not use galvanized container. Kills plants and shrubbery.

CAUTION

TOXIC-IRRITANT. Contains sulfamic acid. May cause burns. Irritates nose, throat and skin. Avoid Contact with skin, eyes and clothing. In case of contact, flush with water for at least 15 minutes; for eyes, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician. If inhaled, remove to fresh air. If difficulty in breathing persists, call a physician. If swallowed, give 1 or 2 glasses of water. Call physician immediately. These precautions apply to both dry form and solution. Kills plants and shrubbery.

**CAUTION! CAUSTIC. USE WITH CARE.
KEEP OUT OF REACH OF CHILDREN.**

FIRST AID

EYES: Immediately flush with plenty of water for at least 15 minutes. Consult a physician.

SKIN: Flush skin with water. Consult a physician if irritation is present.

INGESTION: Drink a lot of water. Contact a physician.

For additional health and safety information please refer to the Safety Data Sheet

Page 1 of 1



Concrete Sealers & Specialty Coatings

Toll-Free: (877) 738-7325
Local: (614) 754-4777
Fax: (614) 754-4778
Emergency: (800) 424-9300

9042 Cotter Street
Green Meadows Commerce Center
Lewis Center, OH 43035
Email: info@vseal.com
www.vseal.com