

SEALER STRIPPER

Premium Concrete Coatings Remover

PRODUCT DESCRIPTION

SEALER STRIPPER is a premium concrete coating remover designed to quickly remove any type of coating from concrete surfaces without harming the concrete itself. SEALER STRIPPER works on acrylic, varnish, latex, lacquer, urethane, epoxy and most any type of coating.

FEATURES

- Powerful formula for fast stripping
- Does not damage concrete
- Easy to use

APPLICATION

Test a small area for results before application. Roll Stripper on concrete. Allow to sit for 10 minutes. If surface is exterior, power wash residue away with water. For interior, use a scrub brush and a flat blade. Do small areas of no more than 100 square feet at a time. Stubborn coatings will require multiple applications of stripper. Clean with CLEMONS DEGREASER NEUTRALIZER and rinse with clean water. NOTE: Timing is critical. Watch for film to lift. Removing too soon will leave coating. If left too long, coating will dry and re-seal.

NET COVERAGE RATE

Use as approximately as many gallons of STRIPPER as gallon of sealer that were applied. If coatings are unknown, use approximately 100 -200 ft² per gallon.

TECHNICAL DATA

VOC: standard 93 g/L

Flash Point: N/A

PRECAUTION

Use safety glasses, rubber gloves, and respirator. Clothe all areas of your body. Avoid breathing vapors. Pre-soak with water and cover any plants that may come in contact with stripper or its residue. Store in cool shaded area. SEALER STRIPPER will develop unsafe pressure in hot areas and will boil at 104°F

CLEANUP

Clean tools with water.

HMIS

HEALTH 2

FLAMMABILITY 1

REACTIVITY 0

PROTECTION G

DISCLAIMER

Since manufacturer has no control over handling, use or storage; no guarantee expressed or implied, is offered. Clemons Concrete Coatings warrants the product to be free of defects and will replace or refund the purchase price of said products proven defective. Labor cost and/or other consequential damages are not covered by this warranty. Responsibility for claims of any kind is strictly limited to the purchase price of the product. The suitability of the product for any extended use shall be solely up to the user.



Concrete Sealers & Concrete Coatings

Toll-Free: (877) 738-7325
Local: (614) 754-4777
Fax: (614) 754-4778
Emergency: (800) 424-9300

9042 Cotter Street
Green Meadows Commerce Center
Lewis Center, OH 43035
Email: info@vseal.com
www.vseal.com